



**Gypsum Plaster** - The surface should be roughened up using a wire brush or other abrasive tool as this will remove the surface laitance. Ensure surface is clean and free from loose matter and prime with two neat coats of ROCATEX Acrylic Primer. Substrate curing before tiling can commence is approximately 4 weeks.

**Plaster Boards** - Prime with two coats of ROCATEX Acrylic Primer diluted 1:1 with clean water.

**Plywood** - Prime the surface with ROCATEX Acrylic Primer diluted 1:1 with clean water.

**Tongue & Groove Boards/Floorboards** - Prime the surface with ROCATEX Acrylic Primer diluted 1:1 with clean water.

**Chipboard** - Apply a neat coat of ROCATEX Acrylic Primer to all exposed edges and joints and apply a slurry coat to the surface: 1 part cement adhesive powder to 1 part ROCATEX Acrylic Primer, apply a thin coat with a brush and allow to dry.

**Cement Based Tile Backer Boards** - Priming is not required if the surface is clean and free from all loose matter. Please note that priming is recommended prior to applying a self levelling compound.

**Existing Tiles & Other Non-Porous Substrates** - Apply slurry coat: 1 part cement adhesive powder to 1 part ROCATEX Acrylic Primer, apply a thin coat with a brush and allow to dry. N.B. We cannot guarantee this method on bitumen.

**Metal** - Score the surface to provide a key. Ensure surface is clean, firm, dry, free from all loose matter including dust, dirt, oil, grease, paint and any other contaminants that may affect adhesion. Apply slurry coat: 1 part cement adhesive powder to 1 part ROCATEX Acrylic Primer, apply a thin coat with a brush and allow to dry.

## COVERAGE

Approx. 10m<sup>2</sup> per kg.

Depending on the absorbency and nature of the substrate, coverage and drying times will vary.

## STORAGE

Store unopened, clear of the ground in a cool, dry, frost free environment. Shelf life is 18 months from date of manufacture. A small amount of liquid may form on the surface of the material, this can be readily remixed by stirring. If the container is left open for a period of time a skin will form over the material. This skin should be removed and not mixed into the product.

## TECHNICAL DATA

Form:	Milky solution
Colour:	Yellow
Specific Gravity:	1.00 - 1.05
pH:	7.00 - 9.00
Flashpoint:	None
Solids Content:	>50
Application Temp. Range:	5°C to 25°C
Service Temp. Range:	-15°C to 75°C
Durability:	Up to 15 years when used as recommended.
Shelf Life:	Up to 18 months when stored in unopened containers, under cool dry conditions. Avoid frost.
Compatibility:	Can be used in contact with most building and decorating materials but should not be used against bituminous materials.
Limitations:	Should not be used in conditions of continuous immersion, below ground level, in areas of high abrasion (e.g. floor joints).