



DeltaBoard

Cement coated, multi-purpose, lightweight, waterproof, thermal construction / tile backer board

- Multi-Purpose Construction Board
- Lightweight, Strong & Easy to Use
- Ultimate Bond with Cement Based Adhesives
- Thermally Insulating / 100% Waterproof
- Impact Sound Reduction / Fireproof
- Manufactured in the UK
- Wide Range of Sizes / 4mm - 80mm
- Interior / Exterior / Domestic / Commercial

DESCRIPTION

DeltaBoard is a waterproof, thermal tile backer board which provides the perfect substrate for all wall and floor tiling applications. Available from only 4mm thick for floors and 10mm for walls, it reduces unwanted build-up and is capable of holding more than double the weight of ply and over three times the weight of skimmed plaster.

DeltaBoard is manufactured in the UK using high density extruded polystyrene which provides excellent insulating properties. The extruded polystyrene core has a factory applied reinforced cement coating which promotes a perfect bond with cement based adhesives and levelling compounds whilst offering excellent impact strength, sound reduction and fire resistance

UNDERFLOOR HEATING

With its excellent thermal properties and impressive U-values, DeltaBoard is essential when installing electric underfloor heating. Heat mats and cables can be laid out easily over the durable reinforced cement coated surface, whilst the high density extruded polystyrene core provides excellent insulating properties, resulting in faster heat up times and greatly reduced downward heat loss.

WATERPROOFING

DeltaBoard is completely resistant to water making it an ideal choice for use in areas subject to prolonged or permanent water immersion such as showers, bathrooms, wetrooms, pool areas etc. When used in conjunction with ROCATEX Waterproof Tanking Coat and Waterproof Sealing Tapes, DeltaBoard forms part of a high performance waterproofing system giving you complete peace of mind. A full range of shower trays is also available.

SOUND REDUCTION

DeltaBoard is the ideal solution where impact sound reduction is of particular importance. Designed for tiled floor areas where noise is an issue, its low mass helps to absorb impact sound energy, giving enhanced acoustic performance.

APPLICATION

DeltaBoard is available in various sizes and thicknesses from 4mm to 80mm. It is easy to use and can be fixed using ROCATEX S1 flexible tile adhesive (solvent based or ready mixed adhesives MUST NOT be used). Alternatively DeltaBoard can be fixed using screws and washers or dowels. Once fixed, DeltaBoard provides a perfect surface on which to apply all types of tiles. For full installation and fixing instructions, please ask for further information.

ROCATEX

Rocatex Ltd
3+4 Camwal Park
Camwal Road
Harrogate, HG1 4PT

T: +44 (0)1423 882 990
F: +44 (0)1423 299 040
E: info@rocatex.com
www.rocatex.com

This information is offered without guarantee. Our Company policy is one of continuous research and development, we therefore reserve the right to update this information at any time without prior notice. We guarantee the consistent high quality of our products, however, as we have no control over site conditions or the execution of the work, we accept no liability for any loss or damage which may arise as a result thereof. If in doubt, conduct a small test or obtain further technical advice.

SIZES AVAILABLE

Board Size L x W (mm)	Available Thicknesses (mm)
1200 x 600	4, 6, 10, 12.5, 20, 30, 40, 50, 60, 70, 80
1200 x 900	12.5
2400 x 600	10, 12.5, 20, 30, 40, 50, 60, 70, 80
2400 x 900	12.5
2400 x 1200	12.5, 20, 60

Thickness (mm)	Size L x W (mm)	Weight (kg)	U-Value (W/m2K)
4	1200 x 600	2.15	3.75
6	1200 x 600	2.35	3.05
10	1200 x 600	2.37	2.23
12.5	1200 x 600	2.42	1.91
20	1200 x 600	2.59	1.33
30	1200 x 600	2.81	0.95
40	1200 x 600	3.03	0.74
50	1200 x 600	3.25	0.60
60	1200 x 600	3.47	0.51
70	1200 x 600	3.59	0.44
80	1200 x 600	3.91	0.39
10	2400 x 600	4.74	2.23
12.5	2400 x 600	4.84	1.91
20	2400 x 600	5.18	1.33
30	2400 x 600	5.62	0.95
40	2400 x 600	6.06	0.74
50	2400 x 600	6.51	0.60
60	2400 x 600	6.94	0.51
70	2400 x 600	7.38	0.44
80	2400 x 600	7.82	0.39
12.5	2400 x 1200	9.68	1.91
20	2400 x 1200	10.36	1.33
60	2400 x 1200	13.88	0.51
12.5	1200 x 900	3.60	1.91
12.5	2400 x 900	7.20	1.91

TECHNICAL DATA

Compressive Strength (10% deformation) BSEN 826:	300 kPa
Thermal Conductivity to BSEN 13164 (5 years):	0.033 W/mK
Water Absorbtion by volume tested to BSEN 12087:	0.6%
Density (foam core only):	36 kg/m3
Temperature Range:	-50°C, + 75°C
Fire Performance BS 476 part 6,7 surface spread of flames / EN 13501-1:	Class O / Euroclass E
Sound Reduction to BS EN ISO 10140-3 test result based on 6mm board:	(ΔL_w) 19dB

ROCATEX

Rocatex Ltd
3+4 Camwal Park
Camwal Road
Harrogate, HG1 4PT

T: +44 (0)1423 882 990
F: +44 (0)1423 299 040
E: info@rocatex.com
www.rocatex.com

This information is offered without guarantee. Our Company policy is one of continuous research and development, we therefore reserve the right to update this information at any time without prior notice. We guarantee the consistent high quality of our products, however, as we have no control over site conditions or the execution of the work, we accept no liability for any loss or damage which may arise as a result thereof. If in doubt, conduct a small test or obtain further technical advice.